



Time for a Refresh with WaterKote® 2K Matt

Taking care of your timber

Time to turn back the clock.

A Melbourne property owner had 60m2 of tired looking Tasmanian Oak timber spanning the entrance, kitchen and living room of their home. They wanted the timber floor to be a feature of their home once again. An entrance and ground floor they could be proud of.

To achieve the desired result the contractor chose **WaterKote® Sealer** a primer and sealing coat followed by **WaterKote® 2K Matt**. The contractor wanted to use a Waterborne polyurethane system, which was both UV resistance and highly durable while achieving a natural finish.

In preparation the timber floor was fully sanded and then sealed with **WaterKote® Sealer** to ensure subsequent coats remain on the surface therefore maximising the wear layer. The seal coat was followed with 2 coats of **WaterKote® 2K Matt** creating an elegant finish highlighting the natural features of the timber.

The contractor was happy with the feel and use of the product and had confidence when applying the system. Both the home owner and contractor were extremely happy with the finished result.

Restoring this Tasmanian Oak Floor was not only a sustainable flooring option it was also a cost effective solution with minimum disruption compared to replacing it.

WaterKote® - SEALER

1 Component Primer/ Sealing Coat

- Reduces the risk of edge bonding & tannin bleed
- Retains the natural colour of timber
- Subsequent coats remain on the surface maximising the wear layer

WaterKote® 2K MATT

A NEW generation 2 Component water borne polyurethane

- Exceptional flow & levelling
- Full cure: 5-7 days after application. Return to service



For more information:
www.urethanecoatings.com.au
 +61 2 9666 3788

www.urethanecoatings.com.au

Urethane Coatings | 2-4 Green Street Banksmeadow | NSW 2019 Australia
 Tel: 02 9666 3888 | Fax: 02 9666 4805 | Website: www.urethanecoatings.com.au

