

Urethane Coatings A division of Era Polymers Pty Ltd

Chemwatch Hazard Alert Code: 3

Version No: 2.3

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 06/12/2021

Print Date: 06/12/2021

S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	WOOD STAINS
Chemical Name	Not Applicable
Synonyms	ANTIQUÉ BROWN STAIN, BLACK STAIN, JARRAH STAIN, MAHOGANY STAIN, OAK STAIN, RED STAIN, TEAK BROWN STAIN, TEAK GOLD STAIN, WALNUT STAIN

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Product is used to colour wood and to tint MONOTHANE, DUOTHANE, MODIFIED OIL's, and TUNGSEAL.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Era Polymers Pty Ltd
Address	2 - 4 Green Street Banksmeadow NSW Australia
Telephone	+61 (0) 2 9666 3888
Fax	+61 (0) 2 9666 4805
Website	www.urethanecoatings.com.au
Email	sales@urethanecoatings.com.au

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+61 2 9186 1132
Other emergency telephone numbers	+61 1800 951 288

Once connected and if the message is not in your preferred language then please dial 01


SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	S5
Classification [1]	Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Dermal) Category 4, Flammable Liquids Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Reproductive Toxicity Category 1B, Sensitisation (Skin) Category 1, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H319	Causes serious eye irritation.
------	--------------------------------

WOOD STAINS

H312	Harmful in contact with skin.
H227	Combustible liquid.
H335	May cause respiratory irritation.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H360D	May damage the unborn child.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
78-59-1	>70	isophorone
33270-70-1	0-10	C.I. Solvent Red 8
72869-46-6*	0-10	Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2- [(4,5-dihydro-3-methyl- 5-oxo-1-phenyl-1H-pyrazol-4-yl)azolbenzoato(2-)chromate(1-)] (1:1)
12237-22-8	0-10	C.I. Solvent Black 27
61791-14-8	0-2.5	cocoamine, ethoxylated
Not Available	to 100	All other substances - non-hazardous
Legend:		1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available

WOOD STAINS

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▸ Wash out immediately with fresh running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation. <p>For thermal burns:</p> <ul style="list-style-type: none"> ▸ Decontaminate area around burn. ▸ Consider the use of cold packs and topical antibiotics. <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> ▸ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. ▸ Use compresses if running water is not available. ▸ Cover with sterile non-adhesive bandage or clean cloth. ▸ Do NOT apply butter or ointments; this may cause infection. ▸ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> ▸ Cool the burn by immerse in cold running water for 10-15 minutes. ▸ Use compresses if running water is not available. ▸ Do NOT apply ice as this may lower body temperature and cause further damage. ▸ Do NOT break blisters or apply butter or ointments; this may cause infection. ▸ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> ▸ Lay the person flat. ▸ Elevate feet about 12 inches. ▸ Elevate burn area above heart level, if possible. ▸ Cover the person with coat or blanket. ▸ Seek medical assistance. <p>For third-degree burns Seek immediate medical or emergency assistance.</p> <p>In the mean time:</p> <ul style="list-style-type: none"> ▸ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. ▸ Separate burned toes and fingers with dry, sterile dressings. ▸ Do not soak burn in water or apply ointments or butter; this may cause infection. ▸ To prevent shock see above. ▸ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. ▸ Have a person with a facial burn sit up. ▸ Check pulse and breathing to monitor for shock until emergency help arrives.
Inhalation	<ul style="list-style-type: none"> ▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▸ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ▸ For advice, contact a Poisons Information Centre or a doctor. ▸ Urgent hospital treatment is likely to be needed. ▸ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▸ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. ▸ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. <p>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:</p> <ul style="list-style-type: none"> ▸ INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. <p>NOTE: Wear a protective glove when inducing vomiting by mechanical means.</p> <ul style="list-style-type: none"> ▸ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

for simple ketones:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.

Continued...

WOOD STAINS

- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Consider intubation at first sign of upper airway obstruction resulting from oedema.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ Avoid spraying water onto liquid pools. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). ▶ May emit acrid smoke. ▶ Mists containing combustible materials may be explosive. <p>Combustion products include: carbon dioxide (CO₂) nitrogen oxides (NO_x) other pyrolysis products typical of burning organic material.</p> <p>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. May emit poisonous fumes. May emit corrosive fumes.</p> <p>WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.</p>
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes.
---------------------	---

Continued...

WOOD STAINS

	<ul style="list-style-type: none"> ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Wipe up. ▶ Place in a suitable, labelled container for waste disposal.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ No smoking, naked lights or ignition sources. ▶ Increase ventilation. ▶ Stop leak if safe to do so. ▶ Contain spill with sand, earth or vermiculite. ▶ Collect recoverable product into labelled containers for recycling. ▶ Absorb remaining product with sand, earth or vermiculite. ▶ Collect solid residues and seal in labelled drums for disposal. ▶ Wash area and prevent runoff into drains. ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<p>Contains low boiling substance:</p> <p>Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none"> ▶ Check for bulging containers. ▶ Vent periodically ▶ Always release caps or seals slowly to ensure slow dissipation of vapours ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<p>Isophorone:</p> <ul style="list-style-type: none"> ▶ is a peroxidisable liquid which forms unstable and possibly explosive peroxides on exposure to air ▶ reacts with strong oxidisers causing fire, explosion ▶ reacts violently with aldehydes, nitric acid, perchloric acid ▶ on contact with strong reducing agents, including hydrides, cyanides, nitrides, alkali metals, and sulfides, may generate flammable hydrogen gas and heat - may cause explosion ▶ is incompatible (may release flammable gases such as hydrogen) with acids, aldehydes, aliphatic amines, anhydrides, cyanides, strong bases, hydrogen peroxide, isocyanates ▶ attacks some plastics, resins, and rubber <p>Ketones in this group:</p> <ul style="list-style-type: none"> ▶ are reactive with many acids and bases liberating heat and flammable gases (e.g., H₂). ▶ react with reducing agents such as hydrides, alkali metals, and nitrides to produce flammable gas (H₂) and heat. ▶ are incompatible with isocyanates, aldehydes, cyanides, peroxides, and anhydrides. ▶ react violently with aldehydes, HNO₃ (nitric acid), HNO₃ + H₂O₂ (mixture of nitric acid and hydrogen peroxide), and HClO₄ (perchloric acid). ▶ may react with hydrogen peroxide to form unstable peroxides; many are heat- and shock-sensitive explosives. <p>A significant property of most ketones is that the hydrogen atoms on the carbons next to the carbonyl group are relatively acidic when compared to hydrogen atoms in typical hydrocarbons. Under strongly basic conditions these hydrogen atoms may be abstracted to form an enolate anion. This property allows ketones, especially methyl ketones, to participate in condensation reactions with other ketones and aldehydes. This type of condensation reaction is favoured by high substrate concentrations and high pH (greater than 1 wt% NaOH).</p> <ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

WOOD STAINS

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	isophorone	Isophorone	Not Available	Not Available	5 ppm / 28 mg/m3	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
isophorone	12 ppm	33 ppm	200 ppm

Ingredient	Original IDLH	Revised IDLH
isophorone	200 ppm	Not Available
C.I. Solvent Red 8	Not Available	Not Available
Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	Not Available	Not Available
C.I. Solvent Black 27	Not Available	Not Available
cocoamine, ethoxylated	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	D	> 0.1 to ≤ 1 ppm
cocoamine, ethoxylated	E	≤ 0.1 ppm


Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations.</p> <p>Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.</p>										
	<table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)
	Type of Contaminant:	Air Speed:									
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)									
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)									
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)										
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)										
<p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only	
Lower end of the range	Upper end of the range										
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents										
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity										
3: Intermittent, low production.	3: High production, heavy use										
4: Large hood or large air mass in motion	4: Small hood-local control only										
<p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of</p>											

WOOD STAINS

	1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> - frequency and duration of contact, - chemical resistance of glove material, - glove thickness and - dexterity <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> - When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. - When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. - Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. - Contaminated gloves should be replaced. <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> - Excellent when breakthrough time > 480 min - Good when breakthrough time > 20 min - Fair when breakthrough time < 20 min - Poor when glove material degrades <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> - Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. - Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream. ▶ Skin cleansing cream. ▶ Eye wash unit.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-

WOOD STAINS

up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Various colours		
Physical state	Liquid	Relative density (Water = 1)	0.92-0.93
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-8	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	251	Molecular weight (g/mol)	Not Available
Flash point (°C)	85	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Workers exposed to 5-8 ppm isophorone for 1 month complained of fatigue and malaise.</p> <p>The low volatility of isophorone means that high vapour concentrations are unlikely unless material is heated. However the low odour threshold level enhances nuisance value.</p> <p>Eye, nose, throat irritation was reported at concentrations below 5 ppm.</p>
----------------	--

WOOD STAINS

	<p>Nausea, headache, dizziness, faintness, inebriation was reported at concentrations above 200 ppm. Symptoms of exposure through inhalation include headache, dizziness, faintness, inebriation, feelings of suffocation, wheezing, shortness of breath, nausea and vomiting.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Ketone vapours irritate the nose, throat and mucous membrane. High concentrations depress the central nervous system, causing headache, vertigo, poor concentration, sleep and failure of the heart and breathing.</p> <p>The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.</p>
Ingestion	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Swallowing isophorone may lead to irritation of the mouth and throat, headache, abdominal pain, drowsiness, central nervous system depression and unconsciousness.</p> <p>Considered an unlikely route of entry in commercial/industrial environments. If swallowed, the liquid can produce stomach upset, nausea, pain and vomiting.</p>
Skin Contact	<p>Skin contact with the material may be harmful; systemic effects may result following absorption.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>The material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>
Eye	<p>Isophorone vapours may be irritating at concentrations of 40-60 parts per million, with higher concentrations causing more intense irritation. In rabbits, one drop caused inflammation of the eyelids and conjunctiva, excessive secretion of tears, clouding of the cornea and a purulent (pus-laden) discharge which disappeared within 14 days.</p> <p>The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.</p> <p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p>
Chronic	<p>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.</p> <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.</p> <p>Chromium (III) is an essential trace mineral. Chronic exposure to chromium (III) irritates the airways, malnourishes the liver and kidneys, causes fluid in the lungs, and adverse effects on white blood cells, and also increases the risk of developing lung cancer.</p> <p>Chronic exposure to isophorone may cause liver and kidney damage. Animal studies showed that chronic exposure may lead to an increased rate of cancers of the liver and kidney.</p>

WOOD STAINS	TOXICITY	IRRITATION
	Not Available	Not Available
isophorone	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1500 mg/kg ^[2]	Eye (human): 25 ppm/15m
	Inhalation(Mammal) LC50; >7 mg/L4h ^[2]	Eye (rabbit): 0.92 mg - SEVERE
	Oral (Rat) LD50; 2330 mg/kg ^[2]	Eye (rabbit): 100 mg/24h-moderate
		Eye: adverse effect observed (irritating) ^[1]
		Skin (rabbit): 100 mg/24h
		Skin: adverse effect observed (irritating) ^[1]
	Skin: no adverse effect observed (not irritating) ^[1]	
C.I. Solvent Red 8	TOXICITY	IRRITATION
	Oral (Rat) LD50; >2000 mg/kg ^[2]	Not Available
Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2- [(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	TOXICITY	IRRITATION
	Not Available	Not Available
C.I. Solvent Black 27	TOXICITY	IRRITATION
	Oral (Rat) LD50; >5000 mg/kg ^[2]	Eye (rabbit): irritating (transient)**
		Eye (rabbit): non-irritating *
		Skin (rabbit): non-irritating (4h) **
	Skin (rabbit): non-irritating *	

WOOD STAINS

cocoamine, ethoxylated	TOXICITY	IRRITATION
	Oral (Rat) LD50; 750 mg/kg ^[2]	Eye (rabbit): 100 mg - moderate
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	
WOOD STAINS	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.	
ISOPHORONE	No significant acute toxicological data identified in literature search. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. A member or analogue of a group of aliphatic and alicyclic terpenoid tertiary alcohols and structurally related substances generally regarded as safe. Most alicyclic substances used as flavour ingredients are mono- and bicyclic terpenes which occur naturally in a wide variety of foods. With the exception of pulegone, alicyclic substances show very low oral acute toxicity. In most subchronic studies performed on animals, no adverse effects were observed at any dose level.	
C.I. SOLVENT BLACK 27	Positive in Ames Test ** The substance is not clastogenic in human lymphocytes under the experimental conditions REACh Dossier Based on laboratory and animal testing, exposure to the material may result in irreversible effects and mutations in humans. NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.	
COCOAMINE, ETHOXYLATED	<p>Alkyl amine polyalkoxylates are not acutely toxic by the oral and dermal routes of exposure, or via inhalation under normal use conditions. Concentrated materials are generally corrosive, eye and skin irritants and may be dermal sensitizers. There is no evidence that alkyl amine polyalkoxylates are neurotoxic, mutagenic, or clastogenic.</p> <p>Surfactants are surface-active materials that can damage the structural integrity of cellular membranes at high dose levels. Thus, surfactants are often corrosive and irritating in concentrated solutions, as indicated by the acute toxicity studies for these inert materials. It is possible that some of the observed toxicity seen in the repeated studies, such as diarrhea or decreased body weight gain, can be attributed to the corrosive and irritating nature of these surfactants.</p> <p>Generally, lower molecular weight AAPs (lower carbon chain units and less alkoxylation) may potentially be more bioavailable because they may be more easily absorbed and distributed than higher molecular weight compounds. Thus overall, the longer chain carbon amine higher polyalkoxylates should be less bioavailable.</p> <p>There are no dermal absorption data on the AAPs. However, data on functionally and structurally similar surfactants suggest that dermal absorption of the AAPs is likely to be low.</p> <p>Following subchronic exposure to rats, some gastrointestinal irritation was observed, but no specific target organ toxicity or neurotoxicity was seen. In subchronic studies in rats and/or dogs, the most sensitive effects noted were increased mortality, clinical signs (salivation, wheezing, emesis, and/or soft faeces), cataracts, cellular changes in the stomach, and liver effects characterized by enzyme induction, and pigment accumulation in Kupffer cells and bile canaliculi. There was no increased susceptibility to the offspring of rats following in utero exposure in two prenatal developmental toxicity studies. However, there is evidence of increased susceptibility in a reproductive screening study in rats.</p> <p>In rat developmental studies, no adverse fetal effects were seen, even at maternally toxic doses. No effects were observed on estrous cyclicity, spermatogenic endpoints, or testosterone and thyroid levels in a two-generation rat reproduction study. However, reproductive and offspring toxicity were noted for AAPs based on litter loss, increase mean number of unaccounted-for implantation sites and decreased mean number of pups born, live litter size and postnatal survival from birth to LD 4.</p> <p>Very little metabolism information is available for the alkyl amine polyalkoxylates. However, it is possible to predict mammalian metabolism based on studies for the alkyl alcohol alkoxyates, which are another class of surfactants. It has been proposed that the primary metabolic pathway involves the excretion of the polyalkoxylate moiety and conversion of the alkyl amine group to a fatty acid that is then converted via oxidative degradation to carbon dioxide and water. In general, the gastrointestinal absorption of AAPs with relatively short alkoxyate chain lengths is expected to be rapid and extensive, while less absorption is likely for the more extensively polyalkoxylated AAPs with larger molecular weights.</p> <p>No structural alerts for potential carcinogenicity of both a representative alkyl amine polyalkoxylate, as well as a possible metabolite/degradate of alkyl amine polyalkoxylate that had been extensively dealkylated, with the amine group intact have been identified Alkyl amine polyalkoxylates are not expected to be carcinogenic. Therefore a cancer dietary exposure assessment is not necessary to assess cancer risk.</p> <p>The US EPA has not found alkyl amine polyalkoxylates to share a common mechanism of toxicity with any other substances, and alkyl amine polyalkoxylates do not appear to produce a toxic metabolite produced by other substances. For the purposes of this tolerance action, therefore, EPA has assumed that alkyl amine polyalkoxylates do not have a common mechanism of toxicity with other substances</p> <p>Alkyl Amine Polyalkoxylates (JITF CST 4 Inert Ingredients). Human Health Risk Assessment to Support Proposed Exemption from the Requirement of a Tolerance When Used as Inert Ingredients in Pesticide Formulations. June 2009 http://beta.regulations.gov/document/EPA-HQ-OPP-2008-0738-0005</p> <p>Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41.</p> <p>Laboratory testing shows that the fatty acid amide, cocoamide DEA, causes occupational allergic contact dermatitis, and that allergy to this substance is becoming more common.</p> <p>Alkanolamides are manufactured by condensation of diethanolamine and the methyl ester of long chain fatty acids.</p> <p>Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products.</p> <p>Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitizers. The oxidation products also cause irritation.</p> <p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p>	
WOOD STAINS & ISOPHORONE & COCOAMINE, ETHOXYLATED	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.	

WOOD STAINS

WOOD STAINS & ISOPHORONE

For isophorone:

Acute toxicity: In animals, the acute toxicity of isophorone is low to moderate. The tendency of isophorone to accumulate in the body is very low, with most of it being excreted within one day. Isophorone irritates the eye and the airway, but not the skin. It is not sensitizing in animal studies.

Repeat dose toxicity: Animal testing did not show significant toxic effects with repeat doses were given by mouth. Inhalation studies showed eye irritation, with changes to the liver and blood.

Genetic toxicity: Overall, on the basis of all results from testing, it is concluded that isophorone does not cause mutations.

Cancer-causing potential: Animal testing has shown conflicting results regarding the cancer-causing potential of isophorone.

Reproductive toxicity: There is no evidence that indicates isophorone interferes adversely with reproduction.

Developmental toxicity: Even at the highest concentrations used for testing, isophorone was not toxic to the embryo, and did not cause birth defects.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

WOOD STAINS	Endpoint	Test Duration (hr)	Species	Value	Source
		Not Available	Not Available	Not Available	Not Available

isophorone	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	768h	Fish	0.65mg/l	4
	BCF	1008h	Fish	1.1-1.8	7
	EC50	72h	Algae or other aquatic plants	475mg/l	2
	LC50	96h	Fish	90-217mg/l	4
	EC50	48h	Crustacea	117mg/l	1
	EC50	96h	Algae or other aquatic plants	48.392-151.8mg/L	4

C.I. Solvent Red 8	Endpoint	Test Duration (hr)	Species	Value	Source
		Not Available	Not Available	Not Available	Not Available

Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2- [(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	Endpoint	Test Duration (hr)	Species	Value	Source
		Not Available	Not Available	Not Available	Not Available

C.I. Solvent Black 27	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	72h	Algae or other aquatic plants	>1mg/l	2
	EC50	72h	Algae or other aquatic plants	>1mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	>100mg/l	2

cocoamine, ethoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	96h	Fish	0.1mg/l	2
	LC50	96h	Fish	0.1mg/l	2
	EC50	48h	Crustacea	0.17mg/l	2

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

for Isophorone: Log Kow: 1.7-3.34; Koc: 25-384; Henry's atm m³/mol: 5.80E-06; Henry's Law Constant: 0.38 Pa.m³/mol; BCF: 7. Melting Point: -8.1C; Water Solubility: 14.5 g/l @ 20C; Vapor Pressure: 40 Pa @ 20C;

Environmental Fate: The target compartments for isophorone will be the hydrosphere (87.6 %) and atmosphere (11.7 %).

Terrestrial Fate: Sorption of isophorone to soil or sediment organic matter is expected to be low.

Isophorone is expected to be rapidly removed by biodegradation.

WOOD STAINS

Atmospheric Fate: Isophorone is rapidly removed by reaction with ozone with an estimated half-life of 23 minutes. The calculated half-life for photodegradation by reaction with hydroxy radicals is 16 hours.

Aquatic Fate: Evaporation of the substance from surface waters will occur within several days and the main removal mechanisms are expected to be biodegradation and volatilization. Photolytical degradation in surface waters is expected to be of minor and hydrolytic degradation is not to be expected.

Ecotoxicity: Isophorone is not expected to bioaccumulate and is considered to be readily biodegradable. The substance is moderately toxic to sheephead minnow, *Daphnia magna* water fleas, *Scenedesmus subspicatus* algae and to the bacterial constituents of activated sludge. The substance is not acutely toxic to fathead minnow. Predicted-no-effect concentration (PNEC) levels for the terrestrial compartment could not be calculated.

For solvent dyes:

Environmental Fate: Solvent dyes are characterised as non-ionic or neutral dyes, and are hydrophobic in character and thus solubility in water is low, ranging from 0.2 mg/l to 34.3 mg/l. Solvent dyes, like the disperse dyes, are hydrophobic. However, due to their large, complex molecular structure, they have lower vapour pressures than disperse dyes. The partition coefficients (Kow) are very high for the non-ionic dyes (in the range of 420 for Solvent Yellow 1 to 11,220 for Solvent Yellow 2). Biodegradability is reduced due to the molecular size of solvent and disperse dyes (especially azo derivatives, which limits uptake. The rate of biodegradation may be increased when the aromatic rings of the neutral dyes are substituted with hydroxyl, amino, acetamido or nitro groups. While the solvent and disperse dyes have the potential to be volatile, their large, complex molecular structure causes them to have low vapour pressures making volatilization unlikely.

Estimated log BCFs for non-ionic dyes indicate a potential risk of bioaccumulation. As dyes are generally visible in water at low concentrations, this poses an aesthetic problem to the environment. Dyes are formulated to tolerate light and chemicals and thus tend to be highly persistent in natural environments. The release of dyes into the environment may therefore present an ecotoxic hazard, with the potential danger of bioaccumulation through the food chain, which may eventually affect humans.

Ecotoxicity: Indications are that the non-ionic (disperse, mordant and solvent) dyes are toxic and potentially toxic to aquatic organisms. Solvent dyes may even be acutely toxic to aquatic organisms. Algae are generally susceptible to dyes, but this is thought to be as a result of indirect consequences of reduced light availability caused by dyes in the water rather than a direct inhibiting effect. While dyes are prone to fungal oxidation, this is dependent on fungal species, which differ in both catalysing ability and dye preferences. When nutrients are limited, secondary fungal degradation of aromatic structures occurs. While enzyme activity of fungi is optimal when food is limited, supplementation of nutrients is necessary for propagation of the fungi cultures. The effects of the substitutional pattern of the dyes are inconclusive, but it has been suggested that introduction of the functional groups; methyl, nitro, sulfo or acid, weakens the inhibition of bacteria, whereas introduction of chlorine and bromine strengthens the inhibition.

For Chromium: Chromium is poorly absorbed by cells found in microorganisms, plants and animals. Hexavalent chromate anions are readily transported into cells and toxicity is closely linked to the higher oxidation state.

Ecotoxicity - Toxicity in Aquatic Organisms: Chromium is harmful to aquatic organisms in very low concentrations. Organisms consumed by fish species are very sensitive to low levels of chromium. Chromium is toxic to fish although less so in warm water. Marked decreases in toxicity are found with increasing pH or water hardness; changes in salinity have little if any effect. Chromium appears to make fish more susceptible to infection. High concentrations can damage and/or accumulate in various fish tissues and in invertebrates such as snails and worms. Reproduction of water fleas is affected by exposure to 0.01 mg/kg hexavalent chromium/L. Toxicity of chromium in fresh-water organisms resulted in mortality rates of 50%. The most sensitive species to the hexavalent chromium anion are invertebrates, scud, fathead minnow, rainbow trout, cladoceran and water flea vertebrate species and guppy.

Toxicity in Microorganisms: In general, toxicity for most microorganisms occurs in the range of 0.05 -5 mg chromium/kg. Trivalent chromium is less toxic than the hexavalent form. The main signs of toxicity are inhibition of growth and the inhibition of photosynthesis or protein synthesis. Gram-negative soil bacteria are generally more sensitive to hexavalent chromium (1-12 mg/kg) than the gram-positive types. Toxicity to trivalent chromium is not observed at similar levels. Soil microbial transformation processes such as nitrification may be affected by low levels of hexavalent chromium (1 mg/kg). Chromium should not be introduced to municipal sewage treatment facilities.

Toxicity in Plants: Chromium in high concentrations can be toxic for plants. The main feature of chromium intoxication is chlorosis, which is similar to iron deficiency. Chromium affects carbohydrate metabolism and leaf chlorophyll concentration decreases with hexavalent chromium concentration (0.01-1 mg/L). The hexavalent form appears to be more toxic than the trivalent species.

Water Standards: Chromium is identified as a hazardous substance in the Federal (U.S.) Water Pollution Control Act and further regulated by Clean Air Water Act Amendments (US). These regulations apply to discharge. The US Primary drinking water Maximum Contaminant Level (MCL), for chromium, is 0.05 mg/L. (total chromium).

For chromium:

Aquatic Fate - Most chromium released into water will be deposited in the sediment. A small percentage of chromium can be found in soluble and insoluble forms with soluble chromium making up a very small percentage of the total chromium. Most of the soluble chromium is present as chromium (VI) and soluble chromium (III) complexes. In the aquatic phase, chromium (III) occurs mostly as suspended solids adsorbed onto clayish materials, organics, or iron oxide present in water. Soluble forms and suspended chromium can undergo intramedia transport. Chromium (VI) in water will eventually be reduced to chromium (III) by organic matter in the water. This process may be slower depending on the type and amount of organic material present and on the redox condition of the water. The reaction was generally faster under anaerobic than aerobic conditions. The oxidation of chromium (III) to chromium (VI) during chlorination of water was highest in the pH range of 5.5 - 6.0.

Atmospheric Fate: Transport of chromium from water to the atmosphere is not likely, except by transport in windblown sea sprays.

Terrestrial Fate: Ecotoxicity - Bioaccumulation is not expected to occur in rainbow trout. Bioaccumulation in bottom feeder bivalves, such as the oyster, blue mussel, and soft shell clam is low. Chromium ranges from slightly toxic to highly toxic in water fleas. Chromium is not expected to biomagnify in the aquatic food chain. Chromium (III) has very low solubility and low mobility in the environment and low toxicity in living organisms. In these forms, chromium is relatively soluble, mobile, and toxic to living organisms. Plants - Bioaccumulation of chromium from soil to above-ground parts of plants is unlikely. There is no indication of biomagnification of chromium along the terrestrial food chain (soil-plant-animal). Chromium concentration in plants may vary with geographic location. Soil - Chromium (VI) may be present in soil as chromate and chromic acid. The fate of chromium in soil is dependent upon the chromium species, which is a function of redox potential and soil pH. Most commonly, soil chromium is in the chromium (III) state. In deeper, anaerobic soils, chromium (VI) will be reduced to chromium (III) by disulfur and ferrous sulfate in soil. The reduction of chromium (VI) to chromium (III) is possible in aerobic soils that contain appropriate organic energy sources. The reduction of chromium (VI) to chromium (III) is facilitated by low pH. Chromium (VI) may exist in the aerobic zone of some natural soil. The oxidation of chromium (III) to chromium (VI) is facilitated by the presence of low oxidisable organic substances, oxygen, manganese dioxide, and moisture. However, when availability of mobile chromium (III) is low, a large portion of chromium in soil will not be oxidized to chromium (VI), even in the presence of magnesium dioxide and favorable pH. Organic forms of chromium (III) are more easily oxidized than insoluble oxides. Factors affecting the microbial reduction of chromium (VI) to chromium (III) include biomass concentration, initial chromium (VI) concentration, temperature, pH, carbon source, oxidation-reduction potential and the presence of both oxyanions and metal cations. Although high levels of chromium (VI) are toxic to most microbes, several resistant bacterial species have been identified which could ultimately be employed in remediation strategies. Most soil chromium is present mainly as insoluble chromium oxide and H_2O and is not very mobile. Chromium was not found in leachate from soil, possibly because it formed complexes with organic matter. The leachability of chromium (VI) increases as soil pH increases. A small percentage of total chromium in soil exists as soluble chromium (VI) and chromium (III), which are more mobile in soil. Sorption depends primarily on the clay content of the soil and, to a lesser extent, on the amount of iron oxide and the organic content. **Ecotoxicity:** Chromium irreversibly sorbed onto soil will not be bio-available to plants and animals under any condition.

Atmospheric Fate: Chromium in soil may be transported to the atmosphere as an aerosol. The low pH of acid rain may facilitate leaching of acid-soluble chromium (III) and (VI) into soil. In the atmosphere, chromium (VI) may be reduced to chromium (III) at a significant rate if vanadium (V2+, V3+ and VO+), ferrous sulfate, bicarbonate ions and arsenic are present. The estimated half life of atmospheric chromium (VI) reduction to chromium (III) has been reported to be from 16 hrs to about 5 days. **Aquatic Fate:** Surface runoff can transport soluble and bulk precipitates of chromium to surface water. Soluble and unadsorbed chromium (III) and (VI) complexes in soil may leach into groundwater.

For Ketones: Ketones, unless they are alpha, beta-unsaturated ketones, can be considered as narcosis or baseline toxicity compounds.

Aquatic Fate: Hydrolysis of ketones in water is thermodynamically favourable only for low molecular weight ketones. Reactions with water are reversible with no permanent change in the structure of the ketone substrate. Ketones are stable to water under ambient environmental conditions. When pH levels are greater than 10, condensation reactions can occur which produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavourable. Based on its reactions in air, it seems likely that ketones undergo photolysis in water.

Terrestrial Fate: It is probable that ketones will be biodegraded by micro-organisms in soil and water.

Ecotoxicity: Ketones are unlikely to bioconcentrate or biomagnify.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
isophorone	LOW (Half-life = 56 days)	LOW (Half-life = 0.13 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
isophorone	LOW

WOOD STAINS

Ingredient	Bioaccumulation
isophorone	LOW (BCF = 7)

Mobility in soil

Ingredient	Mobility
isophorone	LOW (KOC = 58.32)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▸ Containers may still present a chemical hazard/ danger when empty. ▸ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▸ Reduction ▸ Reuse ▸ Recycling ▸ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> ▸ DO NOT allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority. ▸ Recycle wherever possible or consult manufacturer for recycling options. ▸ Consult State Land Waste Authority for disposal. ▸ Bury or incinerate residue at an approved site. ▸ Recycle containers if possible, or dispose of in an authorised landfill.
-------------------------------------	---

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
isophorone	Not Available
C.I. Solvent Red 8	Not Available
Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	Not Available
C.I. Solvent Black 27	Not Available
cocoamine, ethoxylated	Not Available
All other substances - non-hazardous	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
isophorone	Not Available
C.I. Solvent Red 8	Not Available
Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	Not Available

WOOD STAINS

Product name	Ship Type
ol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1)	
C.I. Solvent Black 27	Not Available
cocoamine, ethoxylated	Not Available
All other substances - non-hazardous	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

isophorone is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	

C.I. Solvent Red 8 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Amines, coco alkyl, ethoxylated, compounds with hydrogen bis[2- [(4,5-dihydro-3-methyl- 5-oxo-1-phenyl-1H-pyraz ol-4-yl)azo]benzoato(2-)]chromate(1-) (1:1) is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

C.I. Solvent Black 27 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

cocoamine, ethoxylated is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	Australian Inventory of Industrial Chemicals (AIIC)
---	---

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
China - IECSC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	06/12/2021
Initial Date	06/12/2016

SDS Version Summary

Version	Date of Update	Sections Updated
1.3	06/12/2021	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Appearance, Chronic Health, Classification, Environmental, Exposure Standard, First Aid (swallowed), Handling Procedure, Ingredients, Personal Protection (hands/feet), Physical Properties, Storage (storage incompatibility), Synonyms

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors

WOOD STAINS

BEI: Biological Exposure Index
AIIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSL: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances